

Doc. no. 1SBD250114E1000

Rev. ind. A

Date 2002-05-27

From Jean-Pierre PELLISSIER

Dept. FRCTL

Phone +33 (0) 4 72 22 17 35 Fax +33 (0) 4 72 22 19 35 E-mail Jean-pierre.pellissier@fr.abb.com

Environmental Information

The purpose of this document is to provide environmental information requested in the procedure for Industrial ^{IT} Enabled level 0.

| Product name | Limit Switches with Reset LS33PR | |
|---------------------------|--|--|
| ABB Identity number | 1SBV022211Rxxxx, 1SBV022212Rxxxx, 1SBV022213Rxxxx, 1SBV022231Rxxxx, 1SBV022232Rxxxx, 1SBV022241Rxxxx | |
| Information provided by | Jean-Pierre PELLISSIER | |
| (Name and e-mail address) | Jean-pierre.pellissier@fr.abb.com | |
| Business area | Low Voltage Products - ATLV | |
| Date | May 2002 | |

1. Related documents

Industrial IT Architecture - Introduction and Definitions, 3BSE023904

Industrial IT Certification Overview, 3BSE023905

Industrial IT Certification Guideline, 3BSE024526

Industrial IT Enabled Level 0 - Information, Introduction and Definitions, 3BSE025934

Ref documents:

http://inside.abb.com/The Insider/Featured Portals/Industrial IT Deployment/06 Product Certification/Document Library

Group Function Sustainability Affairs

Doc. no. 1SBD250114E1000

Rev. ind. A

Date 2002-05-27

2. Environmental Information

2.1 Content of hazardous materials

Declare the presence of hazardous materials in the product. Printed circuit boards are declared separately under 2.1.1 and should be excluded from the declaration in the table below.

| Material | Example application | Yes | No | Quantity/unit Optional ⁽¹⁾ |
|--|---------------------------------------|-----|----|--|
| Lead | Batteries, cables | X | | See 2.2 |
| Cadmium | Batteries, switches, additive in lead | | X | |
| Mercury | Batteries, switches | | X | |
| Beryllium | Contact springs | | X | |
| Brominated flame retardants, e.g: PBB, PBDE, TBBPA | Additive in plastics or rubber | | X | |
| HCFCs, e.g: R 22, R 123, R 141b | Cooling media | | X | |
| SF6, sulphurhexafluoride Breakers | | | X | |
| Polyvinyl chloride, PVC Cables | | | X | |

⁽¹⁾ Strive to declare the quantity. This is optional, however, since it is today sometimes difficult to retrieve such information, especially regarding supplied components.

2.1.1 Printed circuit boards

| | the amount of printed circuit boards used in the product by declaring the total surface: |
|-------------|--|
| | < 1 dm ² |
| | 1-10 dm ² |
| | $> 10 \text{ dm}^2$ |
| \boxtimes | No printed circuit boards used in the product |

1SBD250114E1000

Doc. no. 18 Rev. ind. A

| | | | Date 2002-05-27 | | | | |
|--|-------------|---|--|--|--|--|--|
| | | | | | | | |
| 22 Recu | cling infor | mation | | | | | |
| 2.2 1100) | - | | | | | | |
| | is red | Is recycling information for the product available? | | | | | |
| | | Yes | Ref. Document: | | | | |
| | \boxtimes | No | | | | | |
| | | , please rial is pr | specify, in the table below, the component/part/physical position where the esent: | | | | |
| Material | | | Component/part/physical position | | | | |
| Lead | | | Metal plunger < 0,3% (except for 1SBV020241Rxxxx : 0%) -Contact support <0,05% | | | | |
| Cadmium | | | No | | | | |
| Mercury | | | No | | | | |
| Beryllium | | | No | | | | |
| Brominated flame retardants | | lants | No | | | | |
| HCFCs | | | No | | | | |
| SF6, sulphurhexafluoride Polyvinyl chloride, PVC | | e | No No | | | | |
| | | d/or loss | ses during the operation of the product | | | | |
| | | ergy use mentatio | e and/or losses during operation of the product specified in the product on? | | | | |
| | | No | | | | | |
| | | No | | | | | |
| | X | Not re | elevant | | | | |