

Environmental Product Declaration

Drive^{IT} Low Voltage AC Drive
ACS800 frequency converter, 630 kW power



Organisational framework

ABB Oy, Drives in Finland forms part of ABB's Automation Technologies division. The company develops, manufactures and markets drives for ABB Group customers world-wide and is responsible for several key product groups, including variable-speed AC drives and drive systems for speed control of electric motors.

Environmental management

The ISO 14001 international environmental management standard has been implemented and the Helsinki factory is certified since 1996. Life cycle assessment (LCA) is applied continually to all product development.

Product description

ABB Oy, Drives comprises the following product series

- ACS100 power range 0.12 to 2.2 kW
- ACS140 power range 0.12 to 2.2 kW
- ACS160 power range 0.55 to 2.2 kW
- ACS400 power range 2.2 to 37 kW
- ACS600 power range 1.5 to 4,300 kW
- ACS800 power range 1.1 to 5,600 kW

This document applies to the ACS800-07-0750-7 model which is a 690 V, 630 kW product with protection class IP 21.

Material according to the table below is used for the product:

Type of material	kg / product	kg / kW
Steel	433	0.687
Iron	134	0.212
Copper	153	0.242
Aluminium	77	0.121
Plastics	16	0.025
Other materials	30	0.046

Environmental performance

The data and calculations are in accordance with Product Specific Requirements (PSR) for Variable Speed Electric Drives, which specifies the following baselines for the LCA calculation.

Functional unit

The functional unit for the LCA is 1 kW of rated output power.

System boundaries

The life cycle assessment covers all environmental aspects for extraction and production of raw materials, manufacturing of main parts, assembly, transportation and use of the product, dismantling, fragmentation and disposal and recycling of scrap after end of life. It includes consumption of material and energy resources as well as emissions and waste generation.

Calculations are based on an estimated lifetime of 15 years when operating 5,000 hours per year. A Finnish mix of energy has been used for calculating energy consumption during manufacturing and an OECD mix of energy for calculating energy consumption during use and disposal.

Allocation unit

The factor for allocation of common environmental aspects during manufacturing (such as manufacturing waste) is calculated as used working hours in relation to the total annual production volume for the manufacturing at ABB Oy, Drives and mass for the manufacturing at the suppliers.

Resource utilization

	Manufacturing phase unit / kW	Usage phase unit / kW	Disposal phase unit / kW
Use of non-renewable resources			
Coal kg	1.46	553	-0.79
Aluminium (Al) kg	0.12	0.00	-0.09
Copper (Cu) kg	0.23	0.00	-0.18
Iron (Fe) kg	0.90	0.00	-0.73
Manganese (Mn) kg	0.00	0.00	0.00
Natural Gas kg	0.21	64.5	-0.04
Uranium (U) kg	0.00	0.02	0.00
Oil kg	0.55	57.8	-0.13
Use of renewable resources			
Hydro Power MJ	0.03	107	0.00
Wood kg	0.01	28.4	-0.00

Energy consumption and losses

Energy form	kWh / product			kWh / kW		
	Manufacturing phase	Usage phase	Disposal phase	Manufacturing phase	Usage phase	Disposal phase
Electrical energy	717	1,539,000	-	1.13	2,443	-
Heat energy	391	-	-	0.62	-	-

Electricity mix which was used in the manufacturing phase is defined as being 10 % gas, 31 % hydro, 40 % nuclear, 2 % oil and 17 % stone coal. The average OECD electrical energy is defined as being 13.2 % gas, 15.7 % hydro, 23.2 % nuclear, 7.3 % oil, 32.5 % stone coal, 6 % lignite coal, 1.5 % biomass & waste and 0.6 % other. The resultant resource utilization is shown in the table above.

Waste

	kg / kW
Hazardous waste	
During manufacturing	-
At disposal phase	0.04
Regular waste (to landfill)	
During manufacturing phase	0.02
At disposal phase	0.06

The classification data for emissions are as follows:

Environmental effect	Equivalent unit	Manufacturing phase	Usage phase
Global warming potential GWP	kg CO ₂ / kW	5.88	1,549
Acidification potential AP	kmol H ⁺ / kW	0.00	0.27
Eutrophication	kg O ₂ / kW	0.09	18.0
Ozone depletion potential ODP	kg CFC-11 / kW	0.00	0.00
Photochemical oxidants POCP	kg ethylene / kW	0.00	0.26

Additional qualifying factors

Recycling and disposal

The main parts of the product can be recycled - some parts need to be fragmented to separate different types of material. A list of parts and components that can be fragmented and recycled can be obtained from the manufacturer. See references.

Usage phase in relation to the total

It should be observed that the environmental impact during the usage phase is the most important. As an example, GWP for the usage phase is approximately 260 times larger than GWP for the manufacturing phase.

Category of impact	Usage as % of total
Global warming GWP	99.66 %
Acidification AP	99.71 %
Eutrophication	99.57 %
Ozone depletion ODP	99.94 %
Photochemical oxidants POCP	99.69 %

References

- LCA report, 3AFE 64695908
- PSR 2000:7 for Variable Speed Electric Drives
- ACS800-07 Drives, 500 to 2800 kW
Hardware Manual, 3AFE 64731165
- ACS800 frequency converter, Environmental Information, Recycling Instructions, 3AFE 64557815
- MSR 1999:2 Requirements for Environmental Product Declarations, EPD from the Swedish Environmental Management Council

Glossary

Acidification, AP.

Acidification originates from the emissions of sulphur dioxide and oxides of nitrogen. In the atmosphere, these oxides react with water vapour and form acids which subsequently fall down to the earth in the form of rain or snow, or as dry depositions. Acidification potential translates the quantity of emission of substances into a common measure to compare their contributions to the capacity to release hydrogen ions.

Eutrophication.

Nutrients (mainly nitrogen and phosphorus) from sewage outfalls and fertilised farmland accelerate the growth of algae and other vegetation in water. The degradation of organic material consumes oxygen resulting in oxygen deficiency and fish kill. Nutrifaction potential translates the quantity of emission of substances into a common measure expressed as the oxygen required for the degradation of dead biomass.

Global warming potential, GWP.

Some of the gases in the earth's atmosphere (in particular water vapour and carbon dioxide) have an ability to absorb infrared radiation. They do not prevent sunlight reaching the earth's surface, but they do trap some of the infrared radiation emitted back into space causing an increase in the surface temperature. Global Warming Potential, GWP100, translates the quantity of emission of gases into a common measure to compare their contributions - relative to carbon dioxide - to the absorption of infrared radiation in 100 years perspective.

Life cycle assessment, LCA.

A management tool for appraising and quantifying the total environment impact of products or activities over their entire life cycle of particular materials, processes, products, technologies, services or activities. Life cycle assessment comprises three complementary components - inventory analysis, impact analysis and improvement analysis.

Ozone depletion potential, ODP.

Ozone forms a layer in the stratosphere protecting plants and animals from much of the sun's harmful UV-radiation. The ozone levels have declined as a consequence of CFCs and halons released into the atmosphere. A depletion of the ozone layer will increase the UV-radiation at ground level. Ozone depletion potential, ODP, translates the quantity of emission of gases into a common measure to compare their contributions - relative to CFC-11 (a freon) - to the breakdown of the ozone layer.

Photochemical ozone creation, POCP.

Photochemical ozone or ground level ozone is formed by the reaction of volatile organic compounds and nitrogen oxides in the presence of heat and sunlight. Ground-level ozone forms readily in the atmosphere, usually during hot summer weather. Photochemical ozone creation potential translates the quantity of emission of gases into a common measure to compare their contributions - relative to ethylene - to the formation of photochemical oxidants.



ABB Oy

Drives
P. O. Box 184
FIN - 00381 Helsinki
Finland
Telephone +358 10 22 11
Telefax +358 10 222 2681
www.abb.com/motors&drives