Medium Voltage Products

Motor Circuit Fuses, CMF & CMF-TCU
Rated voltage: 3.6-12 kV
Rated current: 63-315 A

The fuse links type CMF/CMF-TCU can be used for motors circuit protection and they are able to withstand, without deterioration, the repeated surges associated with motor starting. Additionally, thanks to last modification of striker pin functionality that release can be now temperature dependent – Temperature Control Unit (TCU) and the low-loss characteristics of the CMF/CMF-TCU fuses make them especially suitable in compact contactor compartments.




Main features:

– specially designed for motor circuit protection,
– tested according to IEC 60644 which guarantees excellent ability to withstand repeated motor starting conditions,
– high current rating within single body dimensions,
– low minimum breaking current,
– low power losses, specially suitable in compact contactor compartments,
– high breaking capacity,
– available with BS tags,
– high current limitation,
– versions CMF-TCU equipped with Temperature Control Unit, which protects against high temperature in enclosed compartments,
– equipped with medium type striker, which is activated immediately when the fuse-elements melt,
– type tested acc. to IEC 60282-1 and IEC 60644,
– dimensions acc. to IEC 60282-1 and DIN 43625.

Available fuses ratings and dimensions


U_N	I_N	e	D	K	I_1	I_3	R_0	P_N
[kV]	[A]	[mm]	[mm]	–	[kA]	[A]	[mΩ]	[W]
3.6	100	292	65	0.75	50	275	3.20	49
	160	292	65	0.7	50	400	1.92	75
	200	292	87	0.7	50	500	1.40	75
	250	292	87	0.6	50	760	0.97	90
	315RC280	292	87	0.6	50	900	0.81	122
7.2	63	442	65	0.75	50	175	8.50	45
	100	442	65	0.75	50	275	4.86	67
	160	442	65	0.7	50	400	2.92	119
	200	442	87	0.7	50	500	2.12	118
	250	442	87	0.6	50	800	1.48	142
	315RC280	442	87	0.6	50	950	1.23	193
12	63	442	65	0.75	50	190	13.52	77
	100	442	87	0.75	50	275	6.62	103
	160	442	87	0.7	50	480	3.98	155
	200	442	87	0.7	50	560	2.73	173

Legend: U_N – rated voltage, I_N – rated current, e – fuse length, D – fuse diameter, K – K-factor according to IEC 60644, I_1 – maximum tested breaking current, I_3 – minimum breaking current, R_0 – fuse resistance at 20°C, P_N – power loss at rated current.



Fuse-base type UCM
– recommended fuse-base for CMF fuses

Type	Rated voltage [kV]	Max. tested fuse-link current [A]	Fuse length e [mm]
UCM 3.6	3.6	315	292
UCM 7.2/12	7.2/12	315	442



For more information please contact:

ABB Contact Center
tel.: +48 22 22 37 777
e-mail: kontakt@pl.abb.com

ABB Sp. z o.o.
Headquarter
1 Zeganska St.
04-713 Warszawa
Phone: +48 22 22 37 000

ABB Sp. z o.o.
Branch in Przasnysz
59 Leszno Str.
06-300 Przasnysz, Poland
Phone: +48 22 22 38 900
e-mail: marketingmv.plabb@pl.abb.com

www.abb.pl

Note:
We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not accept any responsibility whatsoever for potential errors or possible lack of information in this document. We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of ABB.

Copyright 2015 ABB
All rights reserved

3408PL1292-W2-en. Edition 05.2015

Power and productivity
for a better world™