

System 800xA
PC Toolkit Library for Melody
Human System Interface - Single Flags
User Manual

System Version 6.0

Power and productivity
for a better world™

Purpose

The purpose of this document is to describe the Human System Interface with Faceplates and Graphic Elements of the System 800xA with connectivity to Melody/AC870P. All elements are part of an 800xA System Extension, which will be used mainly in the Petrochemical Industry but also in other Process industries. This document defines the ABB Control System standards for the Human Machine Interface (HMI).

Notice

This document contains information about one or more ABB products and may include a description of or a reference to one or more standards that may be generally relevant to the ABB products. The presence of any such description of a standard or reference to a standard is not a representation that all of the ABB products referenced in this document support all of the features of the described or referenced standard. In order to determine the specific features supported by a particular ABB product, the reader should consult the product specifications for the particular ABB product.

ABB may have one or more patents or pending patent applications protecting the intellectual property in the ABB products described in this document.

The information in this document is subject to change without notice and should not be construed as a commitment by ABB. ABB assumes no responsibility for any errors that may appear in this document.

In no event shall ABB be liable for direct, indirect, special, incidental or consequential damages of any nature or kind arising from the use of this document, nor shall ABB be liable for incidental or consequential damages arising from use of any software or hardware described in this document.

This document and parts thereof must not be reproduced or copied without written permission from ABB, and the contents thereof must not be imparted to a third party nor used for any unauthorized purpose.

The software described in this document is furnished under a license and may be used, copied, or disclosed only in accordance with the terms of such license.

Trademarks

All rights to copyrights, registered trademarks, and trademarks reside with their respective owners.

Copyright © 2003-2015 by ABB. All Rights Reserved

All rights reserved.

Release: 2015-11-10

Document Number: 3BDA033448-600

Table of contents

Human System Interface (Classic Style) 6

1. SFLAG – Single Flag Boolean 6

1.1 Faceplate elements 7
1.1.1 sflag_bool_FE_Main PG2 7
1.1.2 sflag_bool_FE_Trend PG2 8
1.1.3 sflag_bool_FE_Config PG2 9
1.2 Indicators 10
1.3 Aspect Links 10
1.4 Faceplate Buttons 10
1.5 Graphic Elements 11

2. SFLAG – Single Flag Clock 13

2.1 Faceplate Elements 14
2.1.1 sflag_clock_FE_Main PG2 14
2.1.2 sflag_clock_FE_Config PG2 15
2.2 Indicators 15
2.3 Aspect Links 15
2.4 Faceplate Buttons 15
2.5 Graphic Elements 15

3. SFLAG – Single Flag Duration 16

3.1 Faceplate elements 18
3.1.1 sflag_duration_FE_Main PG2 18
3.1.2 sflag_duration_FE_Trend PG2 19
3.1.3 sflag_duration_FE_Config PG2 19
3.2 Indicators 19
3.3 Aspect Links 20
3.4 Faceplate Buttons 20
3.5 Graphic Elements 20

4. SFLAG – Single Flag Integer 22

4.1 Faceplate elements 24
4.1.1 sflag_integer_FE_Main PG2 24
4.1.2 sflag_integer_FE_Trend PG2 25
4.1.3 sflag_integer_FE_Config PG2 25
4.2 Indicators 25
4.3 Aspect Links 26
4.4 Faceplate Buttons 26
4.5 Graphic Elements 26

5. SFLAG – Single Flag Long Duration 28

5.1 Faceplate elements 30
5.1.1 sflag_ld_FE_Main PG2 30
5.1.2 sflag_ld_FE_Config PG2 30
5.2 Indicators 30
5.3 Aspect Links 31
5.4 Faceplate Buttons 31
5.5 Graphic Elements 31

6. SFLAG – Single Flag Packed Boolean 33

6.1 Faceplate elements 35
6.1.1 sflag_pbool_FE_Main PG2 35
6.1.2 sflag_pbool_FE_Config PG2 35

6.2 Indicators 35
6.3 Aspect Links 36
6.4 Faceplate Buttons 36
6.5 Graphic Elements 36

7. SFLAG – Single Flag Real 38

7.1 Faceplate elements 40
7.1.1 sflag_real_FE_Main PG2 40
7.1.2 sflag_real_FE_Trend PG2 41
7.1.3 sflag_real_FE_Config PG2 41
7.2 Indicators 41
7.3 Aspect Links 42
7.4 Faceplate Buttons 42
7.5 Graphic Elements 42

Human System Interface (High Performance Style) 44

8. SFLAG – Single Flag Boolean 44

8.1 Faceplate elements 46
8.1.1 sflag_bool_FE_HPHMI_Main 46
8.1.2 sflag_bool_FE_HPHMI_Trend 47
8.1.3 sflag_bool_FE_HPHMI_Config 48
8.2 Indicators 49
8.3 Aspect Links 49
8.4 Faceplate Buttons 49
8.5 Graphic Elements 50

9. SFLAG – Single Flag Clock 52

9.1 Faceplate Elements 54
9.1.1 sflag_clock_FE_HPHMI_Main 54
9.1.2 sflag_clock_FE_HPHMI_Config 54
9.2 Indicators 54
9.3 Aspect Links 55
9.4 Faceplate Buttons 55
9.5 Graphic Elements 55

10. SFLAG – Single Flag Duration 56

10.1 Faceplate elements 58
10.1.1 sflag_duration_FE_HPHMI_Main 58
10.1.2 sflag_duration_FE_HPHMI_Trend 59
10.1.3 sflag_duration_FE_HPHMI_Config 59
10.2 Indicators 59
10.3 Aspect Links 60
10.4 Faceplate Buttons 60
10.5 Graphic Elements 60

11. SFLAG – Single Flag Integer 62

11.1 Faceplate elements 64
11.1.1 sflag_integer_FE_HPHMI_Main 64
11.1.2 sflag_integer_FE_HPHMI_Trend 65
11.1.3 sflag_integer_FE_HPHMI_Config 65
11.2 Indicators 65
11.3 Aspect Links 66
11.4 Faceplate Buttons 66
11.5 Graphic Elements 66

12. SFLAG – Single Flag Long Duration....68
12.1 Faceplate elements....70
12.1.1 sflag_ld_FE_HPHMI_Main....70
12.1.2 sflag_ld_FE_HPHMI_Config....70
12.2 Indicators....70
12.3 Aspect Links....71
12.4 Faceplate Buttons....71
12.5 Graphic Elements....71
13. SFLAG – Single Flag Packed Boolean....72
13.1 Faceplate elements....75
13.1.1 sflag_pbool_FE_HPHMI_Main....75
13.1.2 sflag_pbool_FE_HPHMI_Config....75
13.2 Indicators....75
13.3 Aspect Links....76
13.4 Faceplate Buttons....76
13.5 Graphic Elements....76
14. SFLAG – Single Flag Real....78
14.1 Faceplate elements....80
14.1.1 sflag_real_FE_HPHMI_Main....80
14.1.2 sflag_real_FE_HPHMI_Trend....81
14.1.3 sflag_real_FE_HPHMI_Config....81
14.2 Indicators....81
14.3 Aspect Links....82
14.4 Faceplate Buttons....82
14.5 Graphic Elements....82

Human System Interface (Classic Style)

1. SFLAG – Single Flag Boolean





Figure: 1-1 Main View *Figure: 1-2 Extended View*

Basic information

Name:	**PCMainFaceplate**
Description:	PC MainFaceplate
Connect type:	Melody AC870P
Object type:	Single Flag Boolean
Library:	-
Min. required 800xA version:	SV5.1RevA
Graphics Builder version:	PG2

Table: 1-1 Basic Information

Layout

Parameter	**Value**
Update rate (ms)	1000
Default view	Faceplate
Faceplate orientation	Horizontal

Table: 1-2 Layout information

Sizing information

Parameter in pixels	Main View	Ext. View
Width	250 px	500 px
Height	424 px	424 px
MaxNoOfIndicatorRows	1	1
MaxNoOfIndicatorsRerRow	6	12
MaxNoOfButtonRows	0	0
MaxNoOfButtonPerRow	6	12

Table: 1-3 Sizing Information

Elements

View	Aspect	Tab	NLS-ID	User role
Main	sflag_bool_FE_Main PG2	1	NLSID_PC_Main	EveryOne
Ext	sflag_bool_FE_Main PG2	1	NLSID_PC_Main	EveryOne
Ext	sflag_bool_FE_Trend PG2	2	NLSID_PC_Trend	EveryOne
Ext	sflag_bool_FE_Config PG2	2	NLSID_PC_Config	EveryOne

Table: 1-4 Faceplate Aspect names

1.1 Faceplate elements

1.1.1 sflag_bool_FE_Main PG2

This is the main view for the Single Flag Boolean object type faceplate.



Figure: 1-3 Main Tab

ID	Comment	Property
A	Indication of binary state (yellow color means active state, red rectangle means alarm)	State: O/SIG Alarm: O/ALARM Texts: O/SIG0, O/SIG1
B	Fill color indicates active alarm of corresponding priority level	Alarm: O/ALARM Color: O/PRI

Table: 1-5 Classic Faceplate Main tab Description

1.1.2 sflag_bool_FE_Trend PG2

This is the trend view for the Single Flag Boolean object type faceplate.



Figure: 1-4 Trend Tab

ID	Comment	Property
A	Indication of module output value (“O” label)	O/SIG

Table: 1-6 Classic Faceplate Trend tab Description

1.1.3 sflag_bool_FE_Config PG2

Operation Lock and Manual Inhibit Write Permissions

The Melody faceplates' configuration tab allows checking **Operation Lock** in order to inhibit operator inputs. All buttons will be grayed out. Refer to document 3BDA033456R51xx Installation and Configuration in order to change the default write permission.

There is no Operation Lock Functionality available for Single Flag types.

Manual Inhibit can be selected to manually inhibit all alarms of this Melody tag.



Figure: 1-5 Config Tab

ID	Comment	Property
A	Text describing the type of the tag	TYPE
B	Character which is providing Melody quality information	QUALITY
C	Text describing the Melody security group to which this tag belongs	SECNAME
D	Text describing the Melody gateway to which this tag belongs	GATEWAY
E	Rectangle indicators are showing inhibition status (Yellow color = On), Manual inhibit buttons allow to manually inhibit the tag	INHB INHBAUTO INHBMAN
F	Information about inhibitor	INHBTAG
G	Text describing Melody area to which tag belongs	AREA
H	Text describing Melody unit to which tag belongs	UNIT

Table: 1-7 Classic Faceplate Config tab Description

1.2 Indicators

Icon	Description	Property (Value)	Position		
			Red	FP	Ext
	Forced	O/SIG:Q=216	1	1	1
	Operator note available		-	-	10

Table: 1-8 Indicators

1.3 Aspect Links

Icon	Description	Aspect	Position		
			Red	FP	Ext
	Operator note	Operator note	6	6	12

Table: 1-9 Aspect Links

1.4 Faceplate Buttons

Icon	Description	Property (Value)	Position		
			Red	FP	Ext
	Set output to false	O/SIG (False)	1	1	1
	Set output to true	O/SIG (True)	2	2	2
	Apply the selected action	-	6	6	12

Table: 1-10 Faceplate Buttons

1.5 Graphic Elements

The following Graphic Elements have the following standard properties and enumeration.

Standard properties

Property	Data type	Default value	Description
EnableInput	Boolean	True	Enables input handling of the element, if false the element it self can't selected.
Name	String	-	Name of the element instance in a graphic display. Is set automatically by the Graphics Builder (Name of the element + index).
Rotation	Rotation	0	Rotation angle
SubscriptionRate	Integer	0	Update rate for all properties subscribed for
Transform	Transform	Empty	Enables animation like scaling, moving and rotation. It is intended only for dynamic values.
Visible	Boolean	True	Visibility of the element in the graphic display.
XPos	Float	-	X position of the upper left corner of the element
YPos	Float	-	Y position of the upper left corner of the element

Table: 1-11 Standard Properties for all Graphic Elements

Graphic Elements based on Melody object type Single Flag Boolean

Example	Graphic Element Name	Description
	sflag_bool_cmd0_op_PG2	Command button „OFF". Push button with apply.
	sflag_bool_cmd0_op_1step_PG2	Command button „OFF". Push button without apply.
	sflag_bool_cmd0_cmd1_op_PG2	Command button "OFF/ON". Push button with apply.

Example	Graphic Element Name	Description
	sflag_bool_cmd1_op_PG2	Command button „ON”. Push button with apply.
	sflag_bool_cmd1_op_1step_PG2	Command button „ON”. Push button without apply.
	sflag_bool_o_value_op_text_pg2	Command “ON/OFF” with text. Push button with apply.
	sflag_bool_o_value_op_text1_pg2	Command “ON/OFF” with text. Push button with apply.
	sflag_bool_o_value_op_text2_pg2	Command “ON/OFF” with text. Push button with apply.
	sflag_bool_o_value_op_text3_pg2	Command “ON/OFF” with text. Push button with apply.
	sflag_bool_o_value_op_text_1step_pg2	Command “ON/OFF” with text. Push button with apply.
	sflag_bool_flap_PG2	Mode icon Flap
	sflag_bool_valve_PG2	Mode icon Valve
	sflag_bool_return_PG2	Mode icon Return for Boolean

Table: 1-12 Melody Single Flag Boolean GE

2. SFLAG – Single Flag Clock



Figure: 2-1 Main View *Figure: 2-2 Extended View*

Basic information

Name:	**PCMainFaceplate**
Description:	PC MainFaceplate
Connect type:	Melody AC870P
Object type:	Single Flag Clock
Library:	-
Min. required 800xA version:	SV5.1RevA
Graphics Builder version:	PG2

Table: 2-1 Basic Information

Layout

Parameter	**Value**
Update rate (ms)	1000
Default view	Faceplate
Faceplate orientation	Horizontal

Table: 2-2 Layout information

Sizing information

Parameter in pixels	Main View	Ext. View
Width	250 px	500 px
Height	424 px	424 px
MaxNoOfIndicatorRows	1	1
MaxNoOfIndicatorsRerRow	6	12
MaxNoOfButtonRows	0	0
MaxNoOfButtonPerRow	6	12

Table: 2-3 Sizing Information

Elements

View	Aspect	Tab	NLS-ID	User role
Main	sflag_clock_FE_Main PG2	1	NLSID_PC_Main	EveryOne
Ext	sflag_clock_FE_Main PG2	1	NLSID_PC_Main	EveryOne
Ext	sflag_clock_FE_Config PG2	2	NLSID_PC_Config	EveryOne

Table: 2-4 Faceplate Aspect names

2.1 Faceplate Elements

2.1.1 sflag_clock_FE_Main PG2

This is the main view for the Single Flag Clock object type faceplate. Operator input is possible and based on access rights to the signals.



Figure: 2-3 Main Tab

ID	Comment	Property
A	Indication of time value	YC/SIG

Table: 2-5 Item Description

2.1.2 sflag_clock_FE_Config PG2

Refer to 1.1.3 sflag_bool_FE_Config PG2

2.2 Indicators

Icon	Description	Property (Value)	Position		
			Red	FP	Ext
	Forced	YC/SIG:Q=216	1	1	1
	Operator note available		-	-	10

Table: 2-6 Indicators

2.3 Aspect Links

Icon	Description	Aspect	Position		
			Red	FP	Ext
	Operator note	Operator note	6	6	12

Table: 2-7 Aspect Links

2.4 Faceplate Buttons

Icon	Description	Property (Value)	Position		
			Red	FP	Ext
	Apply the selected action	-	6	6	12

Table: 2-8 Faceplate Buttons

2.5 Graphic Elements

There are no graphic elements for this object type

3. SFLAG – Single Flag Duration





Figure: 3-1 Main View *Figure: 3-2 Extended View*

Basic information

Name:	**PCMainFaceplate**
Description:	PC MainFaceplate
Connect type:	Melody AC870P
Object type:	Single Flag Duration
Library:	-
Min. required 800xA version:	SV5.1RevA
Graphics Builder version:	PG2

Table: 3-1 Basic Information

Layout

Parameter	**Value**
Update rate (ms)	1000
Default view	Faceplate
Faceplate orientation	Horizontal

Table: 3-2 Layout information

Sizing information

Parameter in pixels	Main View	Ext. View
Width	250 px	500 px
Height	424 px	424 px
MaxNoOfIndicatorRows	1	1
MaxNoOfIndicatorsRerRow	6	12
MaxNoOfButtonRows	0	0
MaxNoOfButtonPerRow	6	12

Table: 3-3 Sizing Information

Elements

View	Aspect	Tab	NLS-ID	User role
Main	sflag_duration_FE_Main PG2	1	NLSID_PC_Main	EveryOne
Ext	sflag_duration_FE_Main PG2	1	NLSID_PC_Main	EveryOne
Ext	sflag_duration_FE_Trend PG2	2	NLSID_PC_Trend	EveryOne
Ext	sflag_duration_FE_Config PG2	2	NLSID_PC_Config	EveryOne

Table: 3-4 Faceplate Aspect names

3.1 Faceplate elements

3.1.1 sflag_duration_FE_Main PG2

This is the main view for the Single Flag Duration object type faceplate. Operator input is possible and based on access rights to the signals.



Figure: 3-3 Main Tab

ID	Comment	Property
A	Indication of time value	YD/SIG
B	Maximum range of time value	Constant: 9h 6m 7s
C	Bar graph presentation of time value	YD/SIG
D	Input of time value	YD/SIG
E	Minimum range of time value	Constant: 0s

Table: 3-5 Classic Faceplate Main tab Description

3.1.2 sflag_duration_FE_Trend PG2

This is the trend view for the Single Flag Duration object type faceplate. The time value is presented as number of seconds.



Figure: 3-4 Classic Faceplate Trend Tab

ID	Comment	Property
A	Indication of module output value (“YD” label)	YD/SIG

Table: 3-6 Classic Faceplate Trend tab Description

3.1.3 sflag_duration_FE_Config PG2

Refer to 1.1.3 sflag_bool_FE_Config PG2

3.2 Indicators

Icon	Description	Property (Value)	Position		
			Red	FP	Ext
	Forced	YD/SIG:Q=216	1	1	1
	Operator note available		-	-	10

Table: 3-7 Indicators

3.3 Aspect Links

Icon	Description	Aspect	Position		
			Red	FP	Ext
	Operator note	Operator note	6	6	12

Table: 3-8 Aspect Links

3.4 Faceplate Buttons

Icon	Description	Property (Value)	Position		
			Red	FP	Ext
	Apply the selected action	-	6	6	12

Table: 3-9 Faceplate Buttons

3.5 Graphic Elements

The following Graphic Elements have the following standard properties and enumeration.

Standard properties

Property	Data type	Default value	Description
EnableInput	Boolean	True	Enables input handling of the element, if false the element it self can't selected.
Name	String	-	Name of the element instance in a graphic display. Is set automatically by the Graphics Builder (Name of the element + index).
Rotation	Rotation	0	Rotation angle
SubscriptionRate	Integer	0	Update rate for all properties subscribed for
Transform	Transform	Empty	Enables animation like scaling, moving and rotation. It is intended only for dynamic values.
Visible	Boolean	True	Visibility of the element in the graphic display.

Property	Data type	Default value	Description
XPos	Float	-	X position of the upper left corner of the element
YPos	Float	-	Y position of the upper left corner of the element

Table: 3-10 Standard Properties for all Graphic Elements

Graphic Elements based on Melody object type SINGLE FLAG DURATION

Example	Graphic Element Name	Description
06h 05m 53s	sflag_duration_numeric_PG2	Indicator text box with numeric formatting displaying duration
06h 05m 53s	sflag_duration_numeric_op_PG2	Indicator text box, that allows operator input, with numeric formatting displaying duration

Table: 3-11 Melody Single Flag Duration GE

4. SFLAG – Single Flag Integer





Figure: 4-1 Main View *Figure: 4-2 Extended View*

Basic information

Name:	**PCMainFaceplate**
Description:	PC MainFaceplate
Connect type:	Melody AC870P
Object type:	Single Flag Integer
Library:	-
Min. required 800xA version:	SV5.1RevA
Graphics Builder version:	PG2

Table: 4-1 Basic Information

Layout

Parameter	**Value**
Update rate (ms)	1000
Default view	Faceplate
Faceplate orientation	Horizontal

Table: 4-2 Layout information

Sizing information

Parameter in pixels	Main View	Ext. View
Width	250 px	500 px
Height	424 px	424 px
MaxNoOfIndicatorRows	1	1
MaxNoOfIndicatorsRerRow	6	12
MaxNoOfButtonRows	0	0
MaxNoOfButtonPerRow	6	12

Table: 4-3 Sizing Information

Indicator and button icons are displayed on dedicated positions. Position 1 is the upper left corner. Position 12 is the lower right corner. Position 0 is not shown.

Elements

View	Aspect	Tab	NLS-ID	User role
Main	sflag_integer_FE_Main PG2	1	NLSID_PC_Main	EveryOne
Ext	sflag_integer_FE_Main PG2	1	NLSID_PC_Main	EveryOne
Ext	sflag_integer_FE_Trend PG2	2	NLSID_PC_Trend	EveryOne
Ext	sflag_integer_FE_Config PG2	2	NLSID_PC_Config	EveryOne

Table: 4-4 Faceplate Aspect names

4.1 Faceplate elements

4.1.1 sflag_integer_FE_Main PG2

This is the main view for the Single Flag Integer object type faceplate. Operator input is possible and based on access rights to the signals.



Figure: 4-3 Main Tab

ID	Comment	Property
A	Indication of integer value	YI/SIG
B	Maximum range of integer value	YI/HIGH
C	Bar graph presentation of integer value	YI/SIG
D	Input of integer value	YI/SIG
E	Minimum range of integer value	YI/LOW
F	Minimum range of integer value	YI/UNITS

Table: 4-5 Classic Faceplate Main tab Description

4.1.2 sflag_integer_FE_Trend PG2

This is the trend view for the Single Flag Integer object type faceplate.

.



Figure: 4-4 Trend Tab

ID	Comment	Property
A	Indication of module output integer value (“YI” label)	YI/SIG

Table: 4-6 Classic Faceplate Trend tab Description

4.1.3 sflag_integer_FE_Config PG2

Refer to 1.1.3 sflag_bool_FE_Config PG2

4.2 Indicators

Icon	Description	Property (Value)	Position		
			Red	FP	Ext
	Forced	YI/SIG:Q=216	1	1	1
	Operator note available		-	-	10

Table: 4-7 Indicators

4.3 Aspect Links

Icon	Description	Aspect	Position		
			Red	FP	Ext
	Operator note	Operator note	6	6	12

Table: 4-8 Aspect Links

4.4 Faceplate Buttons

Icon	Description	Property (Value)	Position		
			Red	FP	Ext
	Apply the selected action	-	6	6	12

Table: 4-9 Faceplate Buttons

4.5 Graphic Elements

The following Graphic Elements have the following standard properties and enumeration.

Standard properties

Property	Data type	Default value	Description
EnableInput	Boolean	True	Enables input handling of the element, if false the element it self can't selected.
Name	String	-	Name of the element instance in a graphic display. Is set automatically by the Graphics Builder (Name of the element + index).
Rotation	Rotation	0	Rotation angle
SubscriptionRate	Integer	0	Update rate for all properties subscribed for
Transform	Transform	Empty	Enables animation like scaling, moving and rotation. It is intended only for dynamic values.
Visible	Boolean	True	Visibility of the element in the graphic display.

Property	Data type	Default value	Description
XPos	Float	-	X position of the upper left corner of the element
YPos	Float	-	Y position of the upper left corner of the element

Table: 4-10 Standard Properties for all Graphic Elements

Graphic Elements based on Melody object type SINGLE FLAG INTEGER

Example	Graphic Element Name	Description
	sflag_integer_valve_PG2	Mode icon Valve for integer
	sflag_integer_bargraph_PG2	Bargraph for integer input/output values
	sflag_integer_duration_PG2	Indicator text box with time duration formatting displaying integer
	sflag_integer_numeric_PG2	Indicator text box with numeric formatting displaying integer
	sflag_integer_numeric_op_PG2	Indicator text box, that allows operator input, with numeric formatting displaying integer

Table: 4-11 Melody Single Flag Integer GE

5. SFLAG – Single Flag Long Duration





Figure: 5-1 Main View *Figure: 5-2 Extended View*

Basic information

Name:	PCMainFaceplate
Description:	PC MainFaceplate
Connect type:	Melody AC870P
Object type:	Single Flag Long Duration
Library:	-
Min. required 800xA version:	SV5.1RevA
Graphics Builder version:	PG2

Table: 5-1 Basic Information

Layout

Parameter	Value
Update rate (ms)	1000
Default view	Faceplate
Faceplate orientation	Horizontal

Table: 5-2 Layout information

Sizing information

Parameter in pixels	Main View	Ext. View
Width	250 px	500 px
Height	424 px	424 px
MaxNoOfIndicatorRows	1	1
MaxNoOfIndicatorsRerRow	6	12
MaxNoOfButtonRows	0	0
MaxNoOfButtonPerRow	6	12

Table: 5-3 Sizing Information

Indicator and button icons are displayed on dedicated positions. Position 1 is the upper left corner. Position 12 is the lower right corner. Position 0 is not shown.

Elements

View	Aspect	Tab	NLS-ID	User role
Main	sflag_ld_FE_Main PG2	1	NLSID_PC_Main	EveryOne
Ext	sflag_ld_FE_Main PG2	1	NLSID_PC_Main	EveryOne
Ext	sflag_ld_FE_Config PG2	2	NLSID_PC_Config	EveryOne

Table: 5-4 Faceplate Aspect names

5.1 Faceplate elements

5.1.1 sflag_ld_FE_Main PG2

This is the main view for the Single Flag Long Duration object type faceplate. Operator input is possible and based on access rights to the signals.



Figure: 5-3 Main Tab

ID	Comment	Property
A	Indication of time value	YL/SIG

Table: 5-5 Classic Faceplate Main tab Description

5.1.2 sflag_ld_FE_Config PG2

Refer to 1.1.3 sflag_bool_FE_Config PG2

5.2 Indicators

Icon	Description	Property (Value)	Position		
			Red	FP	Ext
	Forced	YL/SIG:Q=216	1	1	1
	Operator note available		-	-	10

Table: 5-6 Indicators

5.3 Aspect Links

Icon	Description	Aspect	Position		
			Red	FP	Ext
	Operator note	Operator note	6	6	12

Table: 5-7 Aspect Links

5.4 Faceplate Buttons

Icon	Description	Property (Value)	Position		
			Red	FP	Ext
	Apply the selected action	-	6	6	12

Table: 5-8 Faceplate Buttons

5.5 Graphic Elements

The following Graphic Elements have the following standard properties and enumeration.

Standard properties

Property	Data type	Default value	Description
EnableInput	Boolean	True	Enables input handling of the element, if false the element it self can't selected.
Name	String	-	Name of the element instance in a graphic display. Is set automatically by the Graphics Builder (Name of the element + index).
Rotation	Rotation	0	Rotation angle
SubscriptionRate	Integer	0	Update rate for all properties subscribed for
Transform	Transform	Empty	Enables animation like scaling, moving and rotation. It is intended only for dynamic values.
Visible	Boolean	True	Visibility of the element in the graphic display.
XPos	Float	-	X position of the upper left corner of the element

Property	Data type	Default value	Description
YPos	Float	-	Y position of the upper left corner of the element

Table: 5-9 Standard Properties for all Graphic Elements

Graphic Elements based on Melody object type SINGLE FLAG LONG DURATION

Example	Graphic Element Name	Description
06h 05m 53s	sflag_ld_numeric_PG2	Indicator text box with numeric formatting displaying long duration
06h 05m 53s	sflag_ld_numeric_op_PG2	Operable indicator text box with numeric formatting displaying long duration

Table: 5-10 Melody Single Flag Long Duration GE

6. SFLAG – Single Flag Packed Boolean





Figure: 6-1 Main View *Figure: 6-2 Extended View*

Basic information

Name:	**PCMainFaceplate**
Description:	PC MainFaceplate
Connect type:	Melody AC870P
Object type:	Single Flag Packed Boolean
Library:	-
Min. required 800xA version:	SV5.1RevA
Graphics Builder version:	PG2

Table: 6-1 Basic Information

Layout

Parameter	**Value**
Update rate (ms)	1000
Default view	Faceplate
Faceplate orientation	Horizontal

Table: 6-2 Layout information

Sizing information

Parameter in pixels	Main View	Ext. View
Width	250 px	500 px
Height	424 px	424 px
MaxNoOfIndicatorRows	1	1
MaxNoOfIndicatorsRerRow	6	12
MaxNoOfButtonRows	0	0
MaxNoOfButtonPerRow	6	12

Table: 6-3 Sizing Information

Indicator and button icons are displayed on dedicated positions. Position 1 is the upper left corner. Position 12 is the lower right corner. Position 0 is not shown.

Elements

View	Aspect	Tab	NLS-ID	User role
Main	sflag_pbool_FE_Main PG2	1	NLSID_PC_Main	EveryOne
Ext	sflag_pbool_FE_Main PG2	1	NLSID_PC_Main	EveryOne
Ext	sflag_pbool_FE_Config PG2	2	NLSID_PC_Config	EveryOne

Table: 6-4 Faceplate Aspect names

6.1 Faceplate elements

6.1.1 sflag_pbool_FE_Main PG2

This is the main view for the Single Flag Packed Boolean object type faceplate. Operator input is possible and based on access rights to the signals.



Figure: 6-3 Main Tab

ID	Comment	Property
A	Indication of packed boolean value – High and Low word	OP/SIG

Table: 6-5 Classic Faceplate Main tab Description

6.1.2 sflag_pbool_FE_Config PG2

Refer to 1.1.3 sflag_bool_FE_Config PG2

6.2 Indicators

Icon	Description	Property (Value)	Position		
			Red	FP	Ext
	Forced	OP/SIG:Q=216	1	1	1
	Operator note available		-	-	10

Table: 6-6 Indicators

6.3 Aspect Links

Icon	Description	Aspect	Position		
			Red	FP	Ext
	Operator note	Operator note	6	6	12

Table: 6-7 Aspect Links

6.4 Faceplate Buttons

Icon	Description	Property (Value)	Position		
			Red	FP	Ext
	Apply the selected action	-	6	6	12

Table: 6-8 Faceplate Buttons

6.5 Graphic Elements

The following Graphic Elements have the following standard properties and enumeration.

Standard properties

Property	Data type	Default value	Description
EnableInput	Boolean	True	Enables input handling of the element, if false the element it self can't selected.
Name	String	-	Name of the element instance in a graphic display. Is set automatically by the Graphics Builder (Name of the element + index).
Rotation	Rotation	0	Rotation angle
SubscriptionRate	Integer	0	Update rate for all properties subscribed for
Transform	Transform	Empty	Enables animation like scaling, moving and rotation. It is intended only for dynamic values.
Visible	Boolean	True	Visibility of the element in the graphic display.
XPos	Float	-	X position of the upper left corner of the element

Property	Data type	Default value	Description
YPos	Float	-	Y position of the upper left corner of the element

Table: 6-9 Standard Properties for all Graphic Elements

Graphic Elements based on Melody object type SINGLE FLAG PACKED BOOLEAN

Example	Graphic Element Name	Description
	sflag_pbool_text_PG2	Indicator text box for packed Boolean. 16 different text entries in order of signal OP are possible

Table: 6-10 Melody Single Flag Packed Boolean GE

7. SFLAG – Single Flag Real





Figure: 7-1 Main View *Figure: 7-2 Extended View*

Basic information

Name:	PCMainFaceplate
Description:	PC MainFaceplate
Connect type:	Melody AC870P
Object type:	Single Flag Real
Library:	-
Min. required 800xA version:	SV5.1RevA
Graphics Builder version:	PG2

Table: 7-1 Basic Information

Layout

Parameter	Value
Update rate (ms)	1000
Default view	Faceplate
Faceplate orientation	Horizontal

Table: 7-2 Layout information

Sizing information

Parameter in pixels	Main View	Ext. View
Width	250 px	500 px
Height	424 px	424 px
MaxNoOfIndicatorRows	1	1
MaxNoOfIndicatorsRerRow	6	12
MaxNoOfButtonRows	0	0
MaxNoOfButtonPerRow	6	12

Table: 7-3 Sizing Information

Indicator and button icons are displayed on dedicated positions. Position 1 is the upper left corner. Position 12 is the lower right corner. Position 0 is not shown.

Elements

View	Aspect	Tab	NLS-ID	User role
Main	sflag_real_FE_Main PG2	1	NLSID_PC_Main	EveryOne
Ext	sflag_real_FE_Main PG2	1	NLSID_PC_Main	EveryOne
Ext	sflag_real_FE_Trend PG2	2	NLSID_PC_Trend	EveryOne
Ext	sflag_real_FE_Config PG2	2	NLSID_PC_Config	EveryOne

Table: 7-4 Faceplate Aspect names

7.1 Faceplate elements

7.1.1 sflag_real_FE_Main PG2

This is the main view for the Single Flag Real object type faceplate. Operator input is possible and based on access rights to the signals.



Figure: 7-3 Main Tab

ID	Comment	Property
A	Indication of real value	Y/SIG
B	Maximum range of real value	Y/HIGH
C	Bar graph presentation of real value, input possible	Y/SIG
D	Input of real value	Y/SIG
E	Minimum range of real value	Y/LOW
F	Unit string	Y/UNITS

Table: 7-5 Classic Faceplate Main tab Description

7.1.2 sflag_real_FE_Trend PG2

This is the trend view for the Single Flag Real object type faceplate.

.



Figure: 7-4 Trend Tab

ID	Comment	Property
A	Indication of module output value (“Y” label)	Y/SIG

Table: 7-6 Classic Faceplate Trend tab Description

7.1.3 sflag_real_FE_Config PG2

Refer to 1.1.3 sflag_bool_FE_Config PG2

7.2 Indicators

Icon	Description	Property (Value)	Position		
			Red	FP	Ext
	Forced	Y/SIG:Q=216	1	1	1
	Operator note available		-	-	10

Table: 7-7 Indicators

7.3 Aspect Links

Icon	Description	Aspect	Position		
			Red	FP	Ext
	Operator note	Operator note	6	6	12

Table: 7-8 Aspect Links

7.4 Faceplate Buttons

Icon	Description	Property (Value)	Position		
			Red	FP	Ext
	Apply the selected action	-	6	6	12

Table: 7-9 Faceplate Buttons

7.5 Graphic Elements

The following Graphic Elements have the following standard properties and enumeration.

Standard properties

Property	Data type	Default value	Description
EnableInput	Boolean	True	Enables input handling of the element, if false the element it self can't selected.
Name	String	-	Name of the element instance in a graphic display. Is set automatically by the Graphics Builder (Name of the element + index).
Rotation	Rotation	0	Rotation angle
SubscriptionRate	Integer	0	Update rate for all properties subscribed for
Transform	Transform	Empty	Enables animation like scaling, moving and rotation. It is intended only for dynamic values.
Visible	Boolean	True	Visibility of the element in the graphic display.

Property	Data type	Default value	Description
XPos	Float	-	X position of the upper left corner of the element
YPos	Float	-	Y position of the upper left corner of the element

Table: 7-10 Standard Properties for all Graphic Elements

Graphic Elements based on Melody object type SINGLE FLAG REAL

Example	Graphic Element Name	Description
	sflag_real_bargraph_PG2	Bargraph for real values
	sflag_real_valve_PG2	Mode icon Valve for real
	sflag_real_numeric_PG2	Indicator text box with numeric formatting displaying real
	sflag_real_numeric_op_PG2	Operable indicator text box with numeric formatting displaying real

Table: 7-11 Melody Single Flag Real GE

Human System Interface (High Performance Style)

8. SFLAG – Single Flag Boolean

Figure: 8-1 Main View



Figure: 8-2 Extended View

Basic information

Name:	PCMainFaceplate HPHMI
Description:	PC HPHMI Main Faceplate
Connect type:	Melody AC870P
Object type:	Single Flag Boolean
Library:	PCHighPerformanceHMILib 1.0-0
Min. required 800xA version:	SV5.1RevA
Graphics Builder version:	PG2

Table: 8-1 Basic Information

Layout

Parameter	Value
Update rate (ms)	1000
Default view	Faceplate
Faceplate orientation	Horizontal
Reduced View	Not available

Table: 8-2 Layout information

Sizing information

Parameter in pixels	Main View	Ext. View
Width	250 px	500 px
Height	424 px	424 px
MaxNoOfIndicatorRows	1	1
MaxNoOfIndicatorsRerRow	6	12
MaxNoOfButtonRows	1	1
MaxNoOfButtonPerRow	6	12

Table: 8-3 Sizing Information

Indicator and button icons are displayed on dedicated positions. Position 1 is the upper left corner. Position 12 is the lower right corner. Position 0 is not shown.

Elements

View	Aspect	Tab	NLS-ID	User role
Main	sflag_bool_FE_HPHMI_Main	1	NLSID_PC_Main	EveryOne
Ext	sflag_bool_FE_HPHMI_Main	1	NLSID_PC_Main	EveryOne
Ext	sflag_bool_FE_HPHMI_Trend	2	NLSID_PC_Trend	EveryOne
Ext	sflag_bool_FE_HPHMI_Config	2	NLSID_PC_Config	EveryOne

Table: 8-4 Faceplate Aspect names

8.1 Faceplate elements

8.1.1 sflag_bool_FE_HPHMI_Main

This is the main view for the Single Flag Boolean object type faceplate.



Figure: 8-3 Main Tab

ID	Comment	Property
A	Indication of binary state (white color means active state, red rectangle means alarm)	State: O/SIG Alarm: O/ALARM Texts: O/SIG0, O/SIG1
B	Fill color indicates active alarm	Alarm: O/ALARM Color: O/PRI

Table: 8-5 HPHMI Faceplate Main tab Description

8.1.2 sflag_bool_FE_HPHMI_Trend

This is the Trim curves view for the Single Flag Boolean object type faceplate.



Figure: 8-4 HPHMI Faceplate Trend Tab

ID	Comment	Property
A	Indication of module output value (“O” label)	O/SIG

Table: 8-6 HPHMI Faceplate Trend tab Description

8.1.3 sflag_bool_FE_HPHMI_Config

Operation Lock and Manual Inhibit Write Permissions

The Melody faceplates' configuration tab allows checking **Operation Lock** in order to inhibit operator inputs. All buttons will be grayed out. Refer to document 3BDA033456R51xx Installation and Configuration in order to change the default write permission.

There is no Operation Lock Functionality available for Single Flag types.

Manual Inhibit can be selected to manually inhibit all alarms of this Melody tag.



Figure: 8-5 HPHMI Faceplate Config Tab

ID	Comment	Property
A	Text describing the type of the tag	TYPE
B	Character which is providing Melody quality information	QUALITY
C	Text describing the Melody security group to which this tag belongs	SECNAME
D	Text describing the Melody gateway to which this tag belongs	GATEWAY
E	Binary indicators are showing inhibition status (white color = On)	INHB INHBAUTO INHBMAN
F	Buttons allow to manually inhibit the tag	INHBMAN
G	Information about inhibitor	INHBTAG
H	Text describing Melody area to which tag belongs	AREA
I	Text describing Melody unit to which tag belongs	UNIT

Table: 8-7 HPHMI Faceplate Config tab Description

8.2 Indicators

Icon	Description	Property (Value)	Position		
			Red	FP	Ext
	Forced	O/SIG:Q=216	-	1	1
	Operator note available		-	-	10

Table: 8-8 Indicators

8.3 Aspect Links

Icon	Description	Aspect	Position		
			Red	FP	Ext
	Operator note	Operator note	-	6	12

Table: 8-9 Aspect Links

8.4 Faceplate Buttons

Icon	Description	Property (Value)	Position		
			Red	FP	Ext
	Set output to false	O/SIG (False)	-	1	1
	Set output to true	O/SIG (True)	-	2	2
	Apply the selected action	-	-	6	12

Table: 8-10 Faceplate Buttons

8.5 Graphic Elements

The following Graphic Elements have the following standard properties and enumeration.

Standard properties

Property	Data type	Default value	Description
EnableInput	Boolean	True	Enables input handling of the element, if false the element it self can't selected.
Name	String	-	Name of the element instance in a graphic display. Is set automatically by the Graphics Builder (Name of the element + index).
Rotation	Rotation	0	Rotation angle
SubscriptionRate	Integer	0	Update rate for all properties subscribed for
Transform	Transform	Empty	Enables animation like scaling, moving and rotation. It is intended only for dynamic values.
Visible	Boolean	True	Visibility of the element in the graphic display.
XPos	Float	-	X position of the upper left corner of the element
YPos	Float	-	Y position of the upper left corner of the element

Table: 8-11 Standard Properties for all Graphic Elements

Graphic Elements based on Melody object type Single Flag Boolean

Example	Graphic Element Name	Description
	sflag_bool_HPHMI_AlarmInd	Alarm indication
	sflag_bool_HPHMI_flap	Flap symbol based on binary signal O

Example	Graphic Element Name	Description
	sflag_bool_HPHMI_return	Return symbol based on binary signal O
	sflag_bool_HPHMI_text	Text indication based on binary signal O
	sflag_bool_HPHMI_ valve	Valve symbol based on binary signal O

Table: 8-12 Melody Single Flag Boolean GE

9. SFLAG – Single Flag Clock



Figure: 9-1 Main View



Figure: 9-2 Extended View

Basic information

Name:	PCMainFaceplate HPHMI
Description:	PC HPHMI Main Faceplate
Connect type:	Melody AC870P
Object type:	Single Flag Clock
Library:	PCHighPerformanceHMILib 1.0-0
Min. required 800xA version:	SV5.1RevA
Graphics Builder version:	PG2

Table: 9-1 Basic Information

Layout

Parameter	Value
Update rate (ms)	1000
Default view	Faceplate
Faceplate orientation	Horizontal
Reduced View	Not available

Table: 9-2 Layout information

Sizing information

Parameter in pixels	Main View	Ext. View
Width	250 px	500 px
Height	424 px	424 px
MaxNoOfIndicatorRows	1	1
MaxNoOfIndicatorsRerRow	6	12
MaxNoOfButtonRows	1	1
MaxNoOfButtonPerRow	6	12

Table: 9-3 Sizing Information

Indicator and button icons are displayed on dedicated positions. Position 1 is the upper left corner. Position 12 is the lower right corner. Position 0 is not shown.

Elements

View	Aspect	Tab	NLS-ID	User role
Main	sflag_clock_FE_HPHMI_Main	1	NLSID_PC_Main	EveryOne
Ext	sflag_clock_FE_HPHMI_Main	1	NLSID_PC_Main	EveryOne
Ext	sflag_clock_FE_HPHMI_Confi g	2	NLSID_PC_Config	EveryOne

Table: 9-4 Faceplate Aspect names

9.1 Faceplate Elements

9.1.1 sflag_clock_FE_HPHMI_Main

This is the main view for the Single Flag Clock object type faceplate. Operator input is possible and based on access rights to the signals.



Figure: 9-3 Main Tab

ID	Comment	Property
A	Indication of time value	YC/SIG

Table: 9-5 Item Description

9.1.2 sflag_clock_FE_HPHMI_Config

Refer to 8.1.3 SFLAG – Single Flag Boolean

9.2 Indicators

Icon	Description	Property (Value)	Position		
			Red	FP	Ext
	Forced	YC/SIG:Q=216	-	1	1
	Operator note available		-	-	10

Table: 9-6 Indicators

9.3 Aspect Links

Icon	Description	Aspect	Position		
			Red	FP	Ext
	Operator note	Operator note	-	6	12

Table: 9-7 Aspect Links

9.4 Faceplate Buttons

Icon	Description	Property (Value)	Position		
			Red	FP	Ext
	Apply the selected action	-	-	6	12

Table: 9-8 Faceplate Buttons

9.5 Graphic Elements

There are no HPHMI graphic elements for this object type

10. SFLAG – Single Flag Duration





Figure: 10-1 Main View *Figure: 10-2 Extended View*

Basic information

Name:	PCMainFaceplateHPHMI
Description:	PC HPHMI Main Faceplate
Connect type:	Melody AC870P
Object type:	Single Flag Duration
Library:	PCHighPerformanceHMILib 1.0-0
Min. required 800xA version:	SV5.1RevA
Graphics Builder version:	PG2

Table: 10-1 Basic Information

Layout

Parameter	Value
Update rate (ms)	1000
Default view	Faceplate
Faceplate orientation	Horizontal
Reduced View	Not available

Table: 10-2 Layout information

Sizing information

Parameter in pixels	Main View	Ext. View
Width	250 px	500 px
Height	424 px	424 px
MaxNoOfIndicatorRows	1	1
MaxNoOfIndicatorsRerRow	6	12
MaxNoOfButtonRows	1	1
MaxNoOfButtonPerRow	6	12

Table: 10-3 Sizing Information

Indicator and button icons are displayed on dedicated positions. Position 1 is the upper left corner. Position 12 is the lower right corner. Position 0 is not shown.

Elements

View	Aspect	Tab	NLS-ID	User role
Main	sflag_duration_FE_HPHMI_Main	1	NLSID_PC_Main	EveryOne
Ext	sflag_duration_FE_HPHMI_Main	1	NLSID_PC_Main	EveryOne
Ext	sflag_duration_FE_HPHMI_Trend	2	NLSID_PC_Trend	EveryOne
Ext	sflag_duration_FE_HPHMI_Config	2	NLSID_PC_Config	EveryOne

Table: 10-4 Faceplate Aspect names

10.1 Faceplate elements

10.1.1 sflag_duration_FE_HPHMI_Main

This is the main view for the Single Flag Duration object type faceplate. Operator input is possible and based on access rights to the signals.



Figure: 10-3 Main Tab

ID	Comment	Property
A	Indication of time value	YD/SIG
B	Maximum range of time value	Constant: 9h 6m 7s
C	Bar graph presentation of time value	YD/SIG
D	Minimum range of time value	Constant: 0s

Table: 10-5 HPHMI Faceplate Main tab Description

10.1.2 sflag_duration_FE_HPHMI_Trend

This is the Trim curves view for the Single Flag Duration object type faceplate. The time value is presented as number of seconds.



Figure: 10-4 HPHMI Faceplate Trend Tab

ID	Comment	Property
A	Indication of module output value (“YD” label)	YD/SIG

Table: 10-6 HPHMI Faceplate Trend tab Description

10.1.3 sflag_duration_FE_HPHMI_Config

Refer to 8.1.3 SFLAG – Single Flag Boolean

10.2 Indicators

Icon	Description	Property (Value)	Position		
			Red	FP	Ext
	Forced	YD/SIG:Q=216	-	1	1
	Operator note available		-	-	10

Table: 10-7 Indicators

10.3 Aspect Links

Icon	Description	Aspect	Position		
			Red	FP	Ext
	Operator note	Operator note	-	6	12

Table: 10-8 Aspect Links

10.4 Faceplate Buttons

Icon	Description	Property (Value)	Position		
			Red	FP	Ext
	Apply the selected action	-	-	6	12

Table: 10-9 Faceplate Buttons

10.5 Graphic Elements

The following Graphic Elements have the following standard properties and enumeration.

Standard properties

Property	Data type	Default value	Description
EnableInput	Boolean	True	Enables input handling of the element, if false the element it self can't selected.
Name	String	-	Name of the element instance in a graphic display. Is set automatically by the Graphics Builder (Name of the element + index).
Rotation	Rotation	0	Rotation angle
SubscriptionRate	Integer	0	Update rate for all properties subscribed for
Transform	Transform	Empty	Enables animation like scaling, moving and rotation. It is intended only for dynamic values.
Visible	Boolean	True	Visibility of the element in the graphic display.

Property	Data type	Default value	Description
XPos	Float	-	X position of the upper left corner of the element
YPos	Float	-	Y position of the upper left corner of the element

Table: 10-10 Standard Properties for all Graphic Elements

Graphic Elements based on Melody object type SINGLE FLAG DURATION

Example	Graphic Element Name	Description
	sflag_duration_HPHMI_AlarmInd	Alarm indication
	sflag_duration_HPHMI_numeric	Numeric time indication of signal YD
	sflag_duration_HPHMI_numeric	Operable numeric time indication of signal YD

Table: 10-11 Melody Single Flag Duration GE

11. SFLAG – Single Flag Integer





Figure: 11-1 Main View *Figure: 11-2 Extended View*

Basic information

Name:	**PCMainFaceplate HPHMI**
Description:	PC HPHMI Main Faceplate
Connect type:	Melody AC870P
Object type:	Single Flag Integer
Library:	PCHighPerformanceHMILib 1.0-0
Min. required 800xA version:	SV5.1RevA
Graphics Builder version:	PG2

Table: 11-1 Basic Information

Layout

Parameter	**Value**
Update rate (ms)	1000
Default view	Faceplate
Faceplate orientation	Horizontal
Reduced View	Not available

Table: 11-2 Layout information

Sizing information

Parameter in pixels	Main View	Ext. View
Width	250 px	500 px
Height	424 px	424 px
MaxNoOfIndicatorRows	1	1
MaxNoOfIndicatorsRerRow	6	12
MaxNoOfButtonRows	1	1
MaxNoOfButtonPerRow	6	12

Table: 11-3 Sizing Information

Elements

View	Aspect	Tab	NLS-ID	User role
Main	sflag_integer_FE_HPHMI_Main	1	NLSID_PC_Main	EveryOne
Ext	sflag_integer_FE_HPHMI_Main	1	NLSID_PC_Main	EveryOne
Ext	sflag_integer_FE_HPHMI_Trend	2	NLSID_PC_Trend	EveryOne
Ext	sflag_integer_FE_HPHMI_Config	2	NLSID_PC_Config	EveryOne

Table: 11-4 Faceplate Aspect names

11.1 Faceplate elements

11.1.1 sflag_integer_FE_HPHMI_Main

This is the main view for the Single Flag Integer object type faceplate. Operator input is possible and based on access rights to the signals.



Figure: 11-3 Main Tab

ID	Comment	Property
A	Indication of integer value	YI/SIG
B	Maximum range of integer value	YI/HIGH
C	Bar graph presentation of time value, input possible	YI/SIG
D	Minimum range of integer value	YI/LOW
E	Minimum range of integer value	YI/UNITS

Table: 11-5 HPHMI Faceplate Main tab Description

11.1.2 sflag_integer_FE_HPHMI_Trend

This is the Trim curves view for the Single Flag Integer object type faceplate.

.



Figure: 11-4 HPHMI Faceplate Trend Tab

ID	Comment	Property
A	Indication of module output value (“YI” label)	YI/SIG

Table: 11-6 HPHMI Faceplate Trend tab Description

11.1.3 sflag_integer_FE_HPHMI_Config

Refer to 8.1.3 SFLAG – Single Flag Boolean

11.2 Indicators

Icon	Description	Property (Value)	Position		
			Red	FP	Ext
	Forced	YI/SIG:Q=216	-	1	1
	Operator note available		-	-	10

Table: 11-7 Indicators

11.3 Aspect Links

Icon	Description	Aspect	Position		
			Red	FP	Ext
	Operator note	Operator note	-	6	12

Table: 11-8 Aspect Links

11.4 Faceplate Buttons

Icon	Description	Property (Value)	Position		
			Red	FP	Ext
	Apply the selected action	-	-	6	12

Table: 11-9 Faceplate Buttons

11.5 Graphic Elements

The following Graphic Elements have the following standard properties and enumeration.

Standard properties

Property	Data type	Default value	Description
EnableInput	Boolean	True	Enables input handling of the element, if false the element it self can't selected.
Name	String	-	Name of the element instance in a graphic display. Is set automatically by the Graphics Builder (Name of the element + index).
Rotation	Rotation	0	Rotation angle
SubscriptionRate	Integer	0	Update rate for all properties subscribed for
Transform	Transform	Empty	Enables animation like scaling, moving and rotation. It is intended only for dynamic values.
Visible	Boolean	True	Visibility of the element in the graphic display.

Property	Data type	Default value	Description
XPos	Float	-	X position of the upper left corner of the element
YPos	Float	-	Y position of the upper left corner of the element

Table: 11-10 Standard Properties for all Graphic Elements

Graphic Elements based on Melody object type SINGLE FLAG INTEGER

Example	Graphic Element Name	Description
	sflag_integer_HPHMI_AlarmInd	Alarm indication
	sflag_integer_HPHMI_bargraph	Bargraph indication of output integer value YI
	sflag_integer_HPHMI_numeric	Numeric indication of output integer value YI
	sflag_integer_valve	Valve symbol based on integer output value YI

Table: 11-11 Melody Single Flag Integer GE

12. SFLAG – Single Flag Long Duration



Figure: 12-1 Main View *Figure: 12-2 Extended View*

Basic information

Name:	**PCMainFaceplate HPHMI**
Description:	PC HPHMI Main Faceplate
Connect type:	Melody AC870P
Object type:	Single Flag Long Duration
Library:	PCHighPerformanceHMILib 1.0-0
Min. required 800xA version:	SV5.1RevA
Graphics Builder version:	PG2

Table: 12-1 Basic Information

Layout

Parameter	**Value**
Update rate (ms)	1000
Default view	Faceplate
Faceplate orientation	Horizontal
Reduced View	Not available

Table: 12-2 Layout information

Sizing information

Parameter in pixels	Main View	Ext. View
Width	250 px	500 px
Height	424 px	424 px
MaxNoOfIndicatorRows	1	1
MaxNoOfIndicatorsRerRow	6	12
MaxNoOfButtonRows	1	1
MaxNoOfButtonPerRow	6	12

Table: 12-3 Sizing Information

Elements

View	Aspect	Tab	NLS-ID	User role
Main	sflag_ld_FE_HPHMI_Main	1	NLSID_PC_Main	EveryOne
Ext	sflag_ld_FE_HPHMI_Main	1	NLSID_PC_Main	EveryOne
Ext	sflag_ld_FE_HPHMI_Confi g	2	NLSID_PC_Config	EveryOne

Table: 12-4 Faceplate Aspect names

12.1 Faceplate elements

12.1.1 sflag_ld_FE_HPHMI_Main

This is the main view for the Single Flag Long Duration object type faceplate. Operator input is possible and based on access rights to the signals.



Figure: 12-3 Main Tab

ID	Comment	Property
A	Indication of time value	YL/SIG

Table: 12-5 HPHMI Faceplate Main tab Description

12.1.2 sflag_ld_FE_HPHMI_Config

Refer to 8.1.3 SFLAG – Single Flag Boolean

12.2 Indicators

Icon	Description	Property (Value)	Position		
			Red	FP	Ext
	Forced	YL/SIG:Q=216	-	1	1
	Operator note available		-	-	10

Table: 12-6 Indicators

12.3 Aspect Links

Icon	Description	Aspect	Position		
			Red	FP	Ext
	Operator note	Operator note	-	6	12

Table: 12-7 Aspect Links

12.4 Faceplate Buttons

Icon	Description	Property (Value)	Position		
			Red	FP	Ext
	Apply the selected action	-	-	6	12

Table: 12-8 Faceplate Buttons

12.5 Graphic Elements

The following Graphic Elements have the following standard properties and enumeration.

Standard properties

Property	Data type	Default value	Description
EnableInput	Boolean	True	Enables input handling of the element, if false the element it self can't selected.
Name	String	-	Name of the element instance in a graphic display. Is set automatically by the Graphics Builder (Name of the element + index).
Rotation	Rotation	0	Rotation angle
SubscriptionRate	Integer	0	Update rate for all properties subscribed for
Transform	Transform	Empty	Enables animation like scaling, moving and rotation. It is intended only for dynamic values.
Visible	Boolean	True	Visibility of the element in the graphic display.
XPos	Float	-	X position of the upper left corner of the element

Property	Data type	Default value	Description
YPos	Float	-	Y position of the upper left corner of the element

Table: 12-9 Standard Properties for all Graphic Elements

Graphic Elements based on Melody object type SINGLE FLAG LONG DURATION

Example	Graphic Element Name	Description
	sflag_ld_HPHMI_AlarmInd	Alarm indication
1y 01mo 04d 00h 03m 50s	sflag_ld_HPHMI_numeric	Numeric time indication of output value YL
1y 01mo 04d 00h 03m 50s	sflag_ld_HPHMI_numeric_op	Operable numeric time indication of output value YL

Table: 12-10 Melody Single Flag Long Duration GE

13. SFLAG – Single Flag Packed Boolean

Figure: 13-1 Main View



Figure: 13-2 Extended View

Basic information

Name:	PCMainFaceplate HPHMI
Description:	PC HPHMI Main Faceplate
Connect type:	Melody AC870P
Object type:	Single Flag Packed Boolean
Library:	PCHighPerformanceHMILib 1.0-0
Min. required 800xA version:	SV5.1RevA
Graphics Builder version:	PG2

Table: 13-1 Basic Information

Layout

Parameter	Value
Update rate (ms)	1000
Default view	Faceplate
Faceplate orientation	Horizontal
Reduced View	Not available

Table: 13-2 Layout information

Sizing information

Parameter in pixels	Main View	Ext. View
Width	250 px	500 px
Height	424 px	424 px
MaxNoOfIndicatorRows	1	1
MaxNoOfIndicatorsRerRow	6	12
MaxNoOfButtonRows	1	1
MaxNoOfButtonPerRow	6	12

Table: 13-3 Sizing Information

Indicator and button icons are displayed on dedicated positions. Position 1 is the upper left corner. Position 12 is the lower right corner. Position 0 is not shown.

Elements

View	Aspect	Tab	NLS-ID	User role
Main	sflag_pbool_FE_HPHMI_Main	1	NLSID_PC_Main	EveryOne
Ext	sflag_pbool_FE_HPHMI_Main	1	NLSID_PC_Main	EveryOne

View	Aspect	Tab	NLS-ID	User role
Main	sflag_pbool_FE_HPHMI_Main	1	NLSID_PC_Main	EveryOne
Ext	sflag_pbool_FE_HPHMI_Config	2	NLSID_PC_Config	EveryOne

Table: 13-4 Faceplate Aspect names

13.1 Faceplate elements

13.1.1 sflag_pbool_FE_HPHMI_Main

This is the main view for the Single Flag Packed Boolean object type faceplate. Operator input is possible and based on access rights to the signals.



Figure: 13-3 Main Tab

ID	Comment	Property
A	Indication of packed boolean value – High and Low word	OP/SIG

Table: 13-5 HPHMI Faceplate Main tab Description

13.1.2 sflag_pbool_FE_HPHMI_Config

Refer to 8.1.3 SFLAG – Single Flag Boolean

13.2 Indicators

Icon	Description	Property (Value)	Position		
			Red	FP	Ext
	Forced	OP/SIG:Q=216	-	1	1
	Operator note available		-	-	10

Table: 13-6 Indicators

13.3 Aspect Links

Icon	Description	Aspect	Position		
			Red	FP	Ext
	Operator note	Operator note	-	6	12

Table: 13-7 Aspect Links

13.4 Faceplate Buttons

Icon	Description	Property (Value)	Position		
			Red	FP	Ext
	Apply the selected action	-	-	6	12

Table: 13-8 Faceplate Buttons

13.5 Graphic Elements

The following Graphic Elements have the following standard properties and enumeration.

Standard properties

Property	Data type	Default value	Description
EnableInput	Boolean	True	Enables input handling of the element, if false the element it self can't selected.
Name	String	-	Name of the element instance in a graphic display. Is set automatically by the Graphics Builder (Name of the element + index).
Rotation	Rotation	0	Rotation angle
SubscriptionRate	Integer	0	Update rate for all properties subscribed for
Transform	Transform	Empty	Enables animation like scaling, moving and rotation. It is intended only for dynamic values.
Visible	Boolean	True	Visibility of the element in the graphic display.
XPos	Float	-	X position of the upper left corner of the element

Property	Data type	Default value	Description
YPos	Float	-	Y position of the upper left corner of the element

Table: 13-9 Standard Properties for all Graphic Elements

Graphic Elements based on Melody object type SINGLE FLAG PACKED BOOLEAN

Example	Graphic Element Name	Description
	sflag_pbool_HPHMI_AlarmInd	Alarm indication
	sflag_pbool_HPHMI_text	Text indication (based on active bit of L word)

Table: 13-10 Melody Single Flag Packed Boolean GE

14. SFLAG – Single Flag Real



Figure: 14-1 Main View



Figure: 14-2 Extended View

Basic information

Name:	PCMainFaceplate HPHMI
Description:	PC HPHMI Main Faceplate
Connect type:	Melody AC870P
Object type:	Single Flag Real
Library:	PCHighPerformanceHMILib 1.0-0
Min. required 800xA version:	SV5.1RevA
Graphics Builder version:	PG2

Table: 14-1 Basic Information

Layout

Parameter	Value
Update rate (ms)	1000
Default view	Faceplate
Faceplate orientation	Horizontal
Reduced View	Not available

Table: 14-2 Layout information

Sizing information

Parameter in pixels	Main View	Ext. View
Width	250 px	500 px
Height	424 px	424 px
MaxNoOfIndicatorRows	1	1
MaxNoOfIndicatorsRerRow	6	12
MaxNoOfButtonRows	1	1
MaxNoOfButtonPerRow	6	12

Table: 14-3 Sizing Information

Indicator and button icons are displayed on dedicated positions. Position 1 is the upper left corner. Position 12 is the lower right corner. Position 0 is not shown.

Elements

View	Aspect	Tab	NLS-ID	User role
Main	sflag_real_FE_HPHMI_Main	1	NLSID_PC_Main	EveryOne
Ext	sflag_real_FE_HPHMI_Main	1	NLSID_PC_Main	EveryOne
Ext	sflag_real_FE_HPHMI_Trend	2	NLSID_PC_Trend	EveryOne
Ext	sflag_real_FE_HPHMI_Config	2	NLSID_PC_Config	EveryOne

Table: 14-4 Faceplate Aspect names

14.1 Faceplate elements

14.1.1 sflag_real_FE_HPHMI_Main

This is the main view for the Single Flag Real object type faceplate. Operator input is possible and based on access rights to the signals.



Figure: 14-3 Main Tab

ID	Comment	Property
A	Indication of real value	Y/SIG
B	Maximum range of real value	Y/HIGH
C	Bar graph presentation of real value, input possible	Y/SIG
D	Minimum range of real value	Y/LOW
E	Unit string	Y/UNITS

Table: 14-5 HPHMI Faceplate Main tab Description

14.1.2 sflag_real_FE_HPHMI_Trend

This is the Trim curves view for the Single Flag Real object type faceplate.

.



Figure: 14-4 HPHMI Faceplate Trend Tab

ID	Comment	Property
A	Indication of module output value (“Y” label)	Y/SIG

Table: 14-6 HPHMI Faceplate Trend tab Description

14.1.3 sflag_real_FE_HPHMI_Config

Refer to 8.1.3 SFLAG – Single Flag Boolean

14.2 Indicators

Icon	Description	Property (Value)	Position		
			Red	FP	Ext
	Forced	Y/SIG:Q=216	-	1	1
	Operator note available		-	-	10

Table: 14-7 Indicators

14.3 Aspect Links

Icon	Description	Aspect	Position		
			Red	FP	Ext
	Operator note	Operator note	-	6	12

Table: 14-8 Aspect Links

14.4 Faceplate Buttons

Icon	Description	Property (Value)	Position		
			Red	FP	Ext
	Apply the selected action	-	-	6	12

Table: 14-9 Faceplate Buttons

14.5 Graphic Elements

The following Graphic Elements have the following standard properties and enumeration.

Standard properties

Property	Data type	Default value	Description
EnableInput	Boolean	True	Enables input handling of the element, if false the element it self can't selected.
Name	String	-	Name of the element instance in a graphic display. Is set automatically by the Graphics Builder (Name of the element + index).
Rotation	Rotation	0	Rotation angle
SubscriptionRate	Integer	0	Update rate for all properties subscribed for
Transform	Transform	Empty	Enables animation like scaling, moving and rotation. It is intended only for dynamic values.
Visible	Boolean	True	Visibility of the element in the graphic display.
XPos	Float	-	X position of the upper left corner of the element

Property	Data type	Default value	Description
YPos	Float	-	Y position of the upper left corner of the element

Table: 14-10 Standard Properties for all Graphic Elements

Graphic Elements based on Melody object type SINGLE FLAG REAL

Example	Graphic Element Name	Description
	sflag_real_HPHMI_AlarmInd	Alarm indication
	sflag_real_HPHMI_bargraph	Bargraph indication of output signal Y
	sflag_real_HPHMI_numeric	Numeric indication of output signal Y
	sflag_real_HPHMI_trend	Trend indication of output signal Y
	sflag_real_HPHMI_valve	Valve symbol based on real output signal Y

Table: 14-11 Melody Single Flag Real GE

3BDA033448-600 Germany 2015-11-10

Copyright © 2003-2015 by ABB. All Rights Reserved
® Registered Trademark of ABB.
™ Trademark of ABB.

BU Oil, Gas and Petrochemical
Frankfurt, Germany
www.abb.com/Chemicals