

ROBOTICS

Integrated Force Control Adaptive motion technology



Integrated Force Control is one of the key technologies driving the uptake of industrial robots. ABB's Integrated Force Control function facilitates the ease-ofuse for robots in applications requiring real-time adaptive motion control.

Tactile sensing makes intelligent robots

ABB Integrated Force Control automates complex tasks which once required skilled personnel and advanced fixed automation. The robot is equipped with tactile sensing which save installation costs, shortens programming time, reduces process cycle time and improves quality.

The adaptive functionality of Integrated Force Control can be used in many applications, including assembly, product testing and machining. The technology includes powerful functionality that allows the robot to maintain a constant force between itself and the objects it is working with, which is invaluable in both machining and testing applications. The technology also can be used to adapt the robot's speed upon input from the force sensor. This allows it to follow edges and other contours efficiently, such as in deburring of complex shapes. The tactile functionality of Integrated Force Control can also be used in assembly to search for correct positions using advanced search patterns.

How does it work?

Normally robots are position controlled with a predefined path and speed. With ABB Integrated Force Control, the robot reacts to its surroundings and deviates from the programmed path or speed based on feedback from the force sensor. The adapted movement of the robot is determined by constraints specified to the particular application.

Software features

- Advanced software for force control technology
- Force Control RAPID instructions supporting machining, assembly, testing, etc
- Sensor calibration, load identification, gravity compensation
- Supervision and recovery functions
- Configuration of conditions and constraints
- Process feedback from Force Sensor
- Support any 6° of freedom force torque sensors
- Support any 1° of freedom force sensor
- Functionality to use analogue voltage signal instead of force sensor for FC Speed Change

Assembly applications

With Integrated Force Control automated assembly tasks are now possible using traditional robot automation. Compared with expensive hard automation, robotic solutions offer a lower cost investment and greater degree of flexibility.

Assembly is a very demanding application in which parts with small tolerance's must fit together. With ABB's Integrated Force Control technology parts with very small tolerances can be assembled repeatability without requiring highly accurate and expensive fixtures. Integrated Force Control significantly reduces the risk of assembly failures which may result in production problems or damaged parts. A force controlled robot can be programmed to mimic the movements of a human arm, applying search patterns to find the correct position to assemble the part.

Machining applications

Force Control can be use to improve robotic machining applications such as grinding, polishing, deburring and deflashing. One of the software's features, FC Pressure, allows a robot to grind, polish or buff parts whilst maintaining a constant force between the tool and the work piece. Another feature, FC SpeedChange, enables a robot to deburr or deflash partlines and surfaces of parts at a controlled speed, thereby slowing down when encountering excessive burrs or casting flash. This functionality reduces programming time and cycle times in demanding machining applications, and can also considerably increase tool life.

Product testing applications

Product testing is another application area where tactile sensing has advantages. It can be used for test products, for example car seats, steering wheels, hatches, glowe compartments and other similar parts. A robot equipped with force control can perform repetitive tasks with pre-defined forces and movement patterns. Because the forces and movements can be recorded, highly secure traceability is possible. ABB Integrated Force Control technology provides for flexible robot automation for testing tasks that was once only possible with expensive hard automation.

Other applications

There are many other applications areas where Force Control is being used to solve complex automation

ABB Robotics 1250 Brown Road Auburn Hills, MI 48326 United States

abb.com/robotics

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not accept any responsibility whatsoever for potential errors or possible lack of information in this document. problems with simple and effective solutions. The ability to equip robots with tactile sensing, and combine it with other sensors, like cameras or scanners, gives unlimited possibilities to automate complex tasks which today required skilled personnel.

ABB Integrated Force Sensors

ABB offers a package that contains all the necessary hardware and software to run FC functionality.

The package contains:

- Force sensor, measures all six components of force and torque
- Adapter plate
- Shielded high-flex cable
- Voltage measurement board, measurement interface to IRC5 controller
- Force control software

The force sensor is fully integrated into ABB's hardware and software. The force sensor has a robust design offering high overload & IP65 protection, and is EMC tested. The compact and lightweight design makes it suitable for high precision robotic applications.

ATI Force Sensors

In addition, ABB Force Control can also be used with ATI Force/Torque sensors – models Delta, Theta and Omega – with IP60 or IP65 protection and Viton seals for aggressive environments

Specifications			
	Sensor 165	Sensor 660	Sensor 2500
Fx, Fy	165 N	660 N	2500 N
Fz	495 N	1980 N	6250 N
Mx, My, Mz	15 Nm	60 Nm	400 Nm



We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of ABB. Copyright© 2018 ABB. All rights reserved.