



STANDARD TOLERANCE INFO. ON DR 52016 DIMENSIONS ARE IN INCHES
TOLERANCES - UNLESS SPECIFIED - ± .03

CATALOG # (REF)	AMP	BIL KV	MAX V. KV	UNIT	A	A1	A2	A3	B	H	H1	H2	K	K1	M	N	NI	P	*R	*S	*T	*T1	*T2	U	*V	W	Y	Y1	Z
244-042-501	200	110	17.0	INCH	8.86	14.76	16.46	20.12	3.86	21.02	22.72	23.62	17.36	3.43	22.91	7.32	5.38	9.25	19.69	20.67	0.59	0.98	0.59	3.54	0.71	11.46	2.08	2.69	1.22
244-042-505	600			MM	225	375	418	511	98	534	577	600	441	87	582	186	137	235	500	525	15	25	15	90	18	291	53	69	31
244-042-502	200	110	17.0	INCH	8.86	14.76	16.46	20.12	3.86	21.02	22.72	23.62	17.36	3.43	22.91	7.32	6.46	9.25	19.69	20.67	0.59	0.98	0.59		0.71	11.46	3.00	3.77	1.22
244-042-506	600			MM	225	375	418	511	98	534	577	600	441	87	582	186	164	235	500	525	15	25	15	90	18	291	76	96	31
244-042-503	200	110	17.0	INCH	8.86	14.76	16.46	20.12	3.86	21.02	22.72	23.62	17.36	3.43	22.91	7.32	7.95	9.25	19.69	20.67	0.59	0.98	0.59	3.54	0.71	11.46	4.63	5.26	1.22
244-042-507	600			MM	225	375	418	511	98	534	577	600	441	87	582	186	202	235	500	525	15	25	15	90	18	291	118	134	31

*=MOUNTING HOLE LOCATIONS AND DIAMETERS



Note: This layout drawing includes optional K-Mechanism and Left Extension. The stored energy mechanism (A-Mechanism) has a standard shaft length of 3.5 inches.

REF: VERSARUPTER
EPL 244-042

OUTLINE DRAWING

17 KV BASIC SW ASSY.

ABB Power T & D Company Inc.
Distribution Systems Division

5-20348 2

NO.	REVISIONS	BY & DATE	CHD	APP
2	ADDED ABB BORDER & DETAIL "A"	FAB 5-4-82	HKS 5-4-82	AP 5-4-82
1	(E1033) Include A-mech B-hy 7/25/88	BY & DATE	CHD	APP

SIZE	D	SHT	BI	CONT.	ON	REV.
11	11	11	11	11	11	11
DATE	2/23/88	DATE	2/23/88	DATE	2/23/88	SD
DATE	2/23/88	DATE	2/23/88	DATE	2/23/88	SD

THIS DRAWING IS THE PROPERTY OF ABB POWER T & D COMPANY INC. AND CONTAINS CONFIDENTIAL INFORMATION WHICH MUST NOT BE DUPLICATED, USED, OR DISCLOSED OTHER THAN EXPRESSLY AUTHORIZED BY ABB.