

ASSOCIAZIONE PER LA CERTIFICAZIONE DELLE APPARECCHIATURE ELETTRICHE

via Tito Livio, 5 - 24123 - BERGAMO (Italy)

This Certificate applies only to the apparatus tested. The responsibility for conformity of

any apparatus having the same designation with that

manufacturer or responsible

This certificate has been prepared according to LOVAG

The responsible certification body as member of LOVAG

issues a Certificate of Confor-

mity with the above mentioned

Only integral reproduction of

accompanied by any page(s) on which are stated the tests

performed and the assigned rated characteristics of the

apparatus tested, are

piry of this certificate e ACAE certification

permitted without written

rmission from the LOVAG atory responsible for this

Standard(s) following the exclusive use of LOVAG Test

Instructions wherever

this Certificate or reproductions of this page

(Low Voltage Agreement

Group) Objectives and Operating Principles of mutual

tested rests with the

vendor.

recognition.

applicable.

Certificate.

scheme.

el. +390354175244 fax. +390354534662e-mail: acaecert@tin.it



Certificate of Conformity

LOVAG-Certificate No. IT 08.057
Page 1 of 2

Apparatus

Low voltage switchgear and controlgear assembly - 3 phases + neutral - 415 V (U_e) - 690 V (U_i) - 8 Kv (U_{imp}) - frequency 50 Hz - 2000 A - IP 65 - 65 kA (I_{cw}) 3 sec - 65 kA (I_{cw}) at 415 V

Designation

ArTu K 2500A Switchboard

Manufacturer or responsible vendor ABB S.p.A. – ABB SACE Division

Via Italia, 58 - 23846 Garbagnate Monastero (LC) Italy

Tested for: ABB S.p.A. – ABB SACE Division

Via Italia, 58 - 23846 Garbagnate Monastero (LC) Italy

Tested by: ACAE Laboratory IA 01

The apparatus, constructed in accordance with the description mentioned in the Test Report listed on this Certificate has been subjected to the series of proving tests in accordance with IEC 60439-1 Ed.4.1 (2004) and EN 60439-1 (1999) + A1 (2004)

- Verification of temperature-rise limits (8.2.1)
- Verification of the dielectric properties (8.2.2)
- Verification of the short-circuit withstand strength (8.2.3)
- Verification of clearances and creepage distances (8.2.5)
- Verification of mechanical operation (8.2.6)

The results are shown in the Test Report in accordance to LOVAG. The values obtained and the general performance are considered to comply with the above Standard(s) and to justify the characteristic assigned by the manufacturer as stated below:

415 V (U_e) - 50 Hz - 690 V (U_i) 8 kV (U_{imp}) - IP 65

This document includes Report No.: 07.019-R01

Issue Date: 2008.07.23

Responsible Certification Body: ACAE

SINGERT
ACREMINAMENTO DEGINERAD DI CERTIFICAZIONE E ESPEZIONE

PRD N°070B Signatory of EA and IAF Mutual Recognition Agreements Mauro Marchi

Authorized Signature
Date: 2008.09.30



ASSOCIAZIONE PER LA CERTIFICAZIONE DELLE APPARECCHIATURE ELETTRICHE LOVAG

Via Tito Livio, 5 - 24123 - BERGAMO (Italy)

tel. +390354175244 fax. +390354534662 e-mail: acaecert@tin.it

Certificate of Conformity

LOVAG-Certificate No. IT 08.057
Page 2 of 2

Circuit	Rated current (I _n) A	Test current A	Rated short time withstand current (I _{cw}) kA	Rated conditional short-circuit current (I _{ce}) kA at 415 V
1 G	2000	2000	65 (3")	••
11	160	152		65
12	250	238	=	65
13	630	504		65
14	800	760		65

Responsible Certification Body: ACAE

SINCERT
ACCREDITAMENTO DISCANISANI DI CERTIFICAZIONE E 1992/ONE

PRD N°070B Signatory of EA and IAF Mutual Recognition Agreements Mauro Marchi
 Authorized Signature

Date: 2008.09.30